238 Uptown Silverline™





Silver Blue



Silver Brown



- Sophisticated duo colored square design providing functionality for drying and retaining moisture and debris, while offering an upscale look
- debris, while offering an upscale look.

 A dense heavyweight vinyl backing ensures longevity and minimum movement.
- This rich carpet design is crush resistant and has very good dirt hiding characteristics.
- Suitable for heavy traffic conditions.
- For placement inside entrances in offices, hotels, banks, professional buildings restaurants, department stores.
- Vacuum or use extraction method to clean.
- Free of toxic DOP and DMF.



238 Uptown Silverline™

			PRODUCT SPECIFICATIONS	
Designation Dust (Dust Control Matting		
Description		Absorbent carpet mat		
Туре				
Material				
Тор		Loop pile carpet densely tufted high-low pattern of 100% Decalon® yarns. 1270 grams of yarns per m².		
	Backing	Black vinyl		
Process		Tufted		
Category		Indoor absorbent - Upscale		
Recommended use		Indoor - heavy traffic conditions		
Colours		Silver Blue, Silver Brown, Silver Charcoal		
Weight		4 kg/m²		
Thickness		9,5 mm		
Standard sizes		60 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm		
Custom sizes		N/A		
Special remarks				
			PRODUCT TESTING	
Tests		Norms	Results	
Abrasion resistance			ASTM D3884	
Colour fastness to light		nt	AATCC 16E	
Accelerated wear test by sim floor machine			U.S.	3
Accelerated soiling			U.S.	4,5
Anti-slip			DIN51130 BGR181	
Water retention			U.S	5,4 l/m²
Sanitary epidemiologic test			GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09
Resistance to delamination of the second backing		D3936-02 N/A		
Hardness of backing			D2240-02 70	70 Shore A
Operation of the hexapod tumble drum test		pod tumble drum tester	ASTM D5252-98a	Appearance 3.0
			Color change	3.5
Breaking load			D412	65.2 lb
Elongation				33.6 %
Standard test method for tuft bind of			ASTM D1335-98	10.4 lb
pile yarn floor covering				
			FIRE TESTING	
		Surface Flammability	ASTM D2859	Pass
		Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability			 Recyclable material REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) Contributes to cleaner environment by reducing need of cleaning chemicals 	

